



GENERAL NOTE:

1. ALL DIMENSIONS ARE IN MILLIMETERS & LEVELS ARE IN METERS UNLESS NOTED OTHERWISE.
2. ALL MEASUREMENTS ARE PER SITE CONDITION

SHOP DRAWING APPROVAL STATUS						
A	<input type="checkbox"/> APPROVED	B	<input type="checkbox"/> APPROVED AS NOTED			
C	<input type="checkbox"/> REVISE AND RESUBMIT	D	<input type="checkbox"/> NOT APPROVED			

DISCIPLINE	ARCHITECT	CIVIL / STRUCTURAL ENGINEER	MECHANICAL ENGINEER	ELECTRICAL ENGINEER	MECHANICAL EQUIPMENT ENGINEER	OTHERS
NAME	INITIALS					
SIGNATURE						
DATE						

64mm Fire Door FD120 Single Acting Single Door



REV	DATE	DESCRIPTION	DRAWN	CHKD
REVISIONS				

GENERAL NOTES

Note 1 : Frame material - Hardwood ≥ 650 kg/m³ Density @ 10% m/c ± 2%

Note 2 : Lipping material - Hard wood ≥ 650 kg/m³ Density @ 10% M/C ± 2%

Note 3 : Under cut of door standardized for 6mm.

Note 4 : 3 Intumescent seal 25\*6 mm can be fitted on the frame and door leaf on 3 sides for fire rated doors.

Note 5 : Glue line options for Lipping

Note 6 : Finish can be Paint, Veneers & PVC, Plastic Laminates, Decorative Paper (non metallic foil)

Note 7 : Filing method for door leaf using PU glue

Note 8 : Glue : material : polyurethane adhesive /brand name Tividol 1K, PUR adhesive

DRAWN BY: ID	JOB No.:	DATE: 02/02/2018
CHECKED BY:	SCALE:	SHEET SIZE: A1
SHOP ORD. No.:	REVISION NO.	