

دولة الامارات العربية المتحدة وزارةالداخلية القيادة العامة للدفاع المدني لجنة اعتماد المختبرات العالمية وبيوت الخبرة ومعاهد التدريب

Date: 8th Sept 2015

CERTIFICATE OF COMPLIANCE

This certificate of compliance validates the following			
TEST REPORT NUMBER'Assessment Reports' are not acceptable	AU13014005-1	CERTIFICATE NUMBER	FRTD482
DATE OF ISSUE	27.05.2013	DATE OF ISSUE	12.10.2010 last issued 07.01.2015
DATE OF EXPIRY	N/A	DATE OF EXPIRY	11.10.2015
	Manufact	urer details	
NAME OF FACTORY/ MANUFACTURER	Gulf Trade Link FZCO	NAME OF THE BRAND	Fire Ban
FACTORY ADDRESS / REGION (STREET / TOWN / CITY / COUNTRY)	P.O Box 263127 Jebel Ali Free Zone Dubai UAE	MODEL / NO	Fire Ban Board FD 120
WEBSITE	www.fireban.net	LOGO ON THE PRODUCT	IFCC Label
TEL	04-8847758	EMAIL	gtlfireban@live.com



Pro	ReferenceTest Report page NO	
DESCRIPTION OF THE PRODUCT (TECHNICAL DETAILS FROM TEST REPORT, SUCH AS ACTUAL FIRE RATINGS/DIMENSIONS/THICKNESS/SENSITIVITYETC)	Single acting, single leaf doorset consists of wooden frame with overall dimensions 2300mm x 1000mm. FR leaf size is 2245mm x 906mm x 65mm (w x h x thk) Fire Rated for 120 minutes.	1 & 3
TEST STANDARD (SUCH AS ASTM/BS EN/ DNETC)	BS 476-22:1987	1 & 3
TEST DESCRIPTION	The test assembly was installed in a steel restraint frame then moved in front of the furnace, one door was orientated to open into the furnace and the other to open away and both were built into a concrete masonry partition measuring 3m x 3m. The burners were then ignited and the timer started, the burners were controlled to keep the temperatures within the limits specified in the test standard. After 5 minutes, the furnace pressure was adjusted so that the negative plane was established a max of 1000mm above notional floor level. Door deflection relative to the frame was monitored and recorded during the test.	4
SPECIFICATION OF TEST SPECIMEN	Single Acting, Single Leaf doorset consisting of wooden frame, Architrave, and FR door leaf, 2245mm x 904mm x 65mm, composed of 40mm FireBan FR particle board (Density 650kg/m3), faced with 2 no. of 8mm MgO board (Density 900kg/m3), then by 2 no. of 4mm MDF (Density 750kg/m3) and veneered. Glue used was PVA. One Lorient 25mm x 6mm intumescent fire seal located in the door leaf and one Lorient 40mm x 2mm seal also located in the bottom of the door leaf. Hardwood frame (Density 650kg/m3), section size 130mm x (44mm + 18mm) with two Lorient seals 25mm x 6mm. Doorset was fitted with 4 no. stainless steel hinges (4' x 3' x 3 mm), Fire lock Dorma 771 steel latch & Dorma TS72 Door Closer.	3
TEST RESULT (SUCH AS PASSED CRITERIA/ COMPLIED TO/ DURATION/OBSERVATION/ETC)	The doorset is approved for 120 minutes fire rating as during the test it attained 122 mins Integrity and 122 mins Insulation.	5
PRODUCT APPLICATION GUIDELINE (END USE) (CLEARLY STATE THE END USE WITH	The results relate only to the behavior of the specimen of the element of construction under particular conditions of test. They are not intended to be the sole criteria for assessing the	5



دولة الامارات العربية المتحدة وزارةالداخلية القيادةالعامةالدفاعالمدني لجنة اعتماد المختبرات العالمية وبيوت الخبرة ومعاهد التدريب

SPECIFIC APPLICATION, SUCH AS EXACT FIRE RATING/TO BE INSTALLED IN __/TO BE INSTALLED AT __/TO BE CONNECTED WITH ___/TO BE INSTALLED WITH ___ FTC ALONG WITH ANY WARNINGS SUCH AS NOT TO BE USED IN ___/NOT TO BE INSTALLED AT ___/ NOT TO BE INSTALLED WITH ___ ETC.

potential fire performance of the element in use nor do they reflect the actual behavior in fires.

The test results relate only to the specimen tested. Application of the results to door sets of different dimensions or supported other than by a masonry wall or incorporating different components should be the subject of a design appraisal.

The test result may not be appropriate to situation where the door leaf opens away from the heating conditions.

Laboratory and Certification body details			
NAME OF CERTIFICATION BODY	IFC Certification Ltd	NAME OF TEST FACILITY	Intertek Testing Services Limited
CERTIFICATION BODY ADDRESS / REGION (STREET / TOWN / CITY / COUNTRY)	20 Park Street, Princes Risborough, Buckinghamshire, HP27 9AH, UK	TEST FACILITY ADDRESS / REGION (STREET / TOWN / CITY / COUNTRY)	Shanghai Jinqiao Branch Building T52-8 No. 1201 Gui Qiao Road, Jinqiao Development Area, Pudong District Shanghai 201206
WEBSITE	www.ifccertification.com	WEBSITE	www.intertek.com
TEL	+44 1844 275500	TEL	008618621640683
EMAIL	info@ifccertification.com	EMAIL	Kobe.xu@intertek.com
ACCREDITED BY (NAME OF ACCREDITATION BODY WHICH ISSUED ACCREDITATION TO THE CERTIFICATION BODY, ALONG WITH WEBSITE)	UKAS (United Kingdom Accreditation Service) www.ukas.com	ACCREDITED BY (NAME OF ACCREDITATION BODY WHICH ISSUED ACCREDITATION TO THELABORATORY, ALONG WITH WEBSITE)	International Accreditation Service http://iasonline.org
AS PER (STANDARD TO WHICH THE CERTIFICATION BODYIS ACCREDITEDTO)	IEC/ISO 17065	AS PER (STANDARD TO WHICH YOUR ORGANIZATION IS ACCREDITED TO)	IEC/ISO 17025
VALIDITY (EXPIRY DATE OF CERTIFICATION BODYACCREDITATION)	N/A	VALIDITY (EXPIRY DATE OF LABORATORY ACCREDITATION)	N/A
REFERENCE NUMBER: (CERTIFICATION BODY ACCREDITATION REFERENCE NUMBER TO VERIFY ON THE ACCREDITOR'S WEBSITE)	0175	REFERENCE NUMBER: (THE LABORATORY ACCREDITATION REFERENCE NUMBER TO VERIFY ON THE ACCREDITOR'S WEBSITE)	TL-394
CERTIFICATION MARK			



دولة الامارات العربية المتحدة وزارةالداخلية القيادة العامة للدفاعالمدني لجنة اعتماد المختبرات العالمية وبيوت الخبرة ومعاهد التدريب

(ENDORSEMENT) TO BE SIGNED BY MANUFACTURER			
NAME OF MANUFACTURER'S SIGNATORY		SIGNATURE	
EMAIL / TEL	04-8847758	FACTORY OFFICIAL SEAL	
NOTES: I Undertakethat all data and information provided are genuine and accurate			

(ENDORSEMENT) TO BE SIGNED BY CERTIFICATION BODY			
NAME OF CERTIFICATION BODY SIGNATORY	lan Laithwaite	SIGNATURE	Y de revoite
EMAIL / TEL	lan.laithwaite@ifcgroup.com	CERTIFICATION BODY OFFICIAL SEAL	FC certification
NOTES: I Undertake that all data and information provided are genuine and accurate			

ATTACHMENTS:

COPY OF 'CERTIFICATE OF COMPLIANCE' ISSUED BY CERTIFICATION BODY (OLD OR NEW)