

Stainless Steel Accessories

Flush Bolt - 150mm to 450mm

8060

Application:

- For securing the slave leaf of a pair of doors
- Standard installation requires two flushbolts, morticed into the top and bottom of the door for added security and to prevent the door from warping
- Suitable for use on swing or sliding doors

Operation:

- Sprung lever action that flicks the bolt up and down

Installation:

- Flush installation - discrete, clean and neat
- Radiused corners for simple door preparation and improved styling
- Supplied with fixings for timber doors
- Supplied with a flat locking plate
- Radiused chamfered trigger for smooth edge on finger

Specification:

Reference	8060-150 – 150mm 8060-200 – 200mm 8060-300 – 300mm 8060-450 – 450mm
Width	20.5mm
Length	150mm, 200mm, 300mm, 450mm
Depth	22.5mm
Bolt Projection	15mm
Material	Aluminium



Finishes:

- PL - Polished Brass finish
- SS - Satin Stainless Steel finish
- PSS - Polished Stainless Steel finish
- PA - Polished Aluminium
- SA - Satin Aluminium

Standards:

- Durability - 10,000 cycles
 - Corrosion - 96 hours resistance
 - Security - 100N side load
 - Security - 1 minute resistance to side load (4,500N)
- Included in a successful fire test to BS476 Part 22 to 30 minutes

Ordering Code Example:

J - 8060 150 PL
(Boxed - Product Code - Size - Finish)

